









NLS-UR90 (v2)

PORTABLE DATA COLLECTOR

FEATURES

O Industrial-grade Durability

The NLS-UR90's rugged housing is sealed to IP65 standards for protection against dust and water and withstands 1.2m drops to concrete.

Outstanding RFID Performance

With high-performance E710 UHF reader chip and ingenious software, the NLS-UR90 can achieve a batch read speed of more than 900 tags/second; the reading distance can up to 8

O Long Last Battery Life

The NLS-UR90 is equipped with a 6500mAh battery that provides battery life of up to 10 hours from a single charge. What's more, the battery is changeable to ensure the all-day power supply.

Operator-friendly Pistol Grip

With user-focused ergonomic design, it can provide the most comfort to use for either right- or lefthanded operators.







NLS-UR90(v2)

Performance

Write Distance

UHF Module

Frequency Range

Read Range >12M (Indoor); >8M (Outdoor open space) (@ Alien 9740)

(Read range can be affected by tag and environment)

0-3m

Read Rate ≥900 tags/sec

(Read rate can be affected by tag and environment)

Based on Impinj E710

Antenna Circularly polarized antenna (4dBi), 5dBm-33dBm(±1dBm) adjustable.

FCC (USA): 902-928MHz ETSI (Europe): 865.6-867.6MHz SRRC-MII (China): 920-925MHz

Standards Supported EPC Class 1 Gen 2 (ISO 18000-6C)

Physical/Electrical

Dimensions (L×W×H) $160 \times 83 \times 158$ mm

Weight 390g

User Input Trigger on pistol grip

Environmental

Operating Temperature -20°C to 50°C (-4°F to 13°F)
Storage Temperature -30°C to 70°C (-40°F to 158°F)
Humidity 5% to 95% (non-condensing)

Static Discharge ±15 kV (Air discharge), ±8 kV (Direct discharge)

Drop 1.2m Sealing IP65

Communication

Host Terminal NLS-MT90 (Need to buy separately)

Host Connection 8-pin connector

Specifications are subject to change without notice. 2022/11/17 Version: V1.0

Newland AIDC

Add: No.1 Rujiang West Rd., Mawei, Fuzhou, Fujian 350001, China Tel: +86-591-83979500 Fax: +86-591-83979216 Email: info@newlandaidc.com

Web: www.newlandaidc.com

Asia Pacific

Add: 6 Raffles Quay #14-06 Singapore 048582 Email: info@newlandaidc.com Europe & Middle East

Add: Rolweg 25, 4104 AV Culemborg, The Netherlands Tel: +31 (0) 345 87 00 33 Email: sales@newland-id.com Tech Support: tech-support@newland-id.com North America & Latin America

Add: 46559 Fremont Blvd., Fremont, CA 94538, USA Tel: +1 510 490 3888 Fax: +1 510 490 3887 Email: info@newlandaidc.com

